

BASIC KEY FOB PATTERN

REQUIREMENTS

2 $\frac{1}{2}$ " x 8" piece of fabric

$\frac{3}{4}$ " x 9" piece of wadding

One Swivel clip or D ring or Key hardware

INSTRUCTIONS

Fold $\frac{1}{4}$ " of fabric over on one short end towards the wrong side.

Then fold fabric in half longways RST, sew along the long seam.

Press seam flat so it is in the middle, then turn right side out.

Feed the wadding through the centre

Top stitch $\frac{1}{8}$ " down each side.

If you are using a swivel clip or D ring:

Stop $\frac{1}{2}$ " from the folded end, trim wadding slightly shorter than the length.

Feed swivel clip or D ring onto the fabric.

Stuff raw end into folded end to create a loop – pin – sew in place and then finish the top stitching.

Place the swivel clip/D ring into the seam end and sew or fix in place.

If using hardware:

Fold in half and attach hardware using a pair of pliers to squeeze the edges together – we recommend putting a piece of scrap wadding or fabric to stop the pliers scratching the hardware.

Some different ideas for variations on the basic keyfob:

- Stitch a length of ribbon to your fabric before you sew the back seam
- Decorate the strip with fancy stitches on your machine after you have turned it right sides out
- Piece together the strip before you sew the back seam
-